ULTIMA Slitting Machine



Robust & Versatile, the Wise Choice Slitter








Slitting Machine

Robust & Versatile, the Wise Choice Slitter

ULTIMA Series



Features:

Materials

• LLDPE or HDPE 40-150μ; PE, OPP, CPP or PVC 30-150μ; PET 12-150μ; BOPP 25-150μ; Metalised film 20-70μ; Laminated films 40-200µ; Paper 60-210gsm.

Unwinding Section

- Unwinding-stand with shaftless hydraulic loading clamps.
- Equipped with digital type line position control (LPC) to ensure accurate slitting position.

Specification:

Model No.	SLF-MB130L
Min. & Max. Parent Web Width	650 ~ 1300 mm
Max. Parent Web Diameter	1000 mm
Unwind / Rewind Core I.D.	3" or 6"
Max. Rewind Diameter	600 mm
Min. & Max. Slit Width	50 ~ 650 mm (Depends on various materials' conditions)
Max. Machine Speed	400 M / min.

Slitting Section

- Equipped with razor cutter.
- Equipped with blower, expulsion tube.

Rewinding Section

- Horizontal moveable rewinding stand.
- · Static eliminating device.
- Pneumatic control for lay-on roller provides steadier rewinding tension.

- Rewind stand with open arm system makes unloading easier.
- Equipped with ball type friction rings, which not only can raise the concentricity of the paper cores and finish rolls, but also can make unloading easier without causing paper dust.
- Individual tension detectors for two rewinding sections provide accurate and steady tension control.
- Equipped with taper tension control, providing superior rewind-tension for thin films whose thickness are under 15µ.





Add. No. 69-10, Sec. 2, Chung Shin Rd., Tali Dist., Taichung City 412, Taiwan Tel. +886-4-2483-2477 Fax. +886-4-2483-0852 E-Mail. dahbah@dahbah.com.tw website. www.dahbah.com.tw