# **RE Rewinding Machines**

## Inspection / CCD / Reversible / Wide / Narrow / Splice / Trim reels






**REF-60R** Series





# **Rewinding Inspecting Machines**

#### **REF-Small Roll Series**



#### **Specification :**

Model No.	REF-Small Roll
Max. Parent Web Width	400 / 600 mm
Max. Parent Web Diameter	500 mm
Unwind / Rewind Core I.D.	3" or 6"
Max. Machine Speed	200 M / min.

#### **Features :**

#### Material

• Plastic laminated film 40-150µ.

#### Unwinding / Rewinding Section

- Cantilevered air-shafts (φ3") making loading and unloading easier.
- Equipped with edge position control (EPC) to provide accurate film positioning for unwinding.

#### **Tension Control**

• Equipped with automatic tension controlling system and load-cells.

#### Inspecting Section

- Equipped with inspecting acrylic board and fluorescent lamps, making inspecting easier.
- Synchronize stroboscope with photo sensor.

### **Specification :**

Model No.	REF-Wide Roll
Max. Parent Web Width	1000 / 1300 mm
Max. Parent Web Diameter	800 mm
Unwind / Rewind Core I.D.	3" or 6"
Max. Machine Speed	200 M / min.

### Features :

#### Material

- Plastic laminated film 40-150µ.
  Unwinding / Rewinding Section
- Shaftless type unwinding stand with  $\varphi$ 3" adapters.
- Equipped with digital type line position control (LPC) to provide accurate film positioning for unwinding.

#### Inspecting Section

- Equipped with inspecting acrylic board and fluorescent lamps, making inspecting easier.
- Reversible running.
- Synchronize stroboscope with photo sensor.

#### **Optional Accessories**

- Splicing table with suction device
- Inspecting camera with monitor



The working speed depends on the material condition.
 Due to machine development, above information may change without notice.



Add. No. 69-10, Sec. 2, Chung Shin Rd., Tali Dist., Taichung City 412, Taiwan Tel. +886-4-2483-2477 Fax. +886-4-2483-0852 E-Mail. dahbah@dahbah.com.tw website. www.dahbah.com.tw

